


Standart Features

- Steel construction body
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 6 guide ram
- Ram adjustment with motor
- Hydraulic overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Material and scrap Groove
- Automatic Reversible Fluid Lubrication System
- Foot paddle
- Double hand control
- Single-continious-interrupted shot options
- PLC applied
- Electric counter
- Security PLC
- Compliance with CE directives
- Press Safety Valve
- Ram Cushioning Cylinders

Optional Features

- Speed Control Unit

	Value	Unit
Capacity	150	Ton
Throat Depth	305	mm
Table - Ram Distance	470	mm
Housing Width	570	mm
Ram Adjusment	90	mm
Press Width	1800	mm
Press Height	2900	mm
Press Depth	1800	mm
Table Hole Diameter	Ø205	mm
Table Depth	610	mm
Table Width	950	mm
Die Tie Hole Diameter	Ø50	mm
Ram Face Size	450 × 750	mm
Table Height From Floor	720	mm
Stroke	10-110	mm
Stroke Per Minute	53	spm
Motor Power	15	kW
Motor Speed	1500	rpm
Weight	7700	kg

A3	ISO 128	HP_150_PK_AEP_HS	Technical Specifications		Page
TASARIM / DESIGNED	Taha Canat	26.12.2022			1/1
ÇİZEN / DRAWN	Taha Canat	24.01.2023			
KONTROL / CHECKED					