



**Standart Features**

- Steel construction body
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 6 guide ram
- Ram adjustment with motor
- Hydraulic overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Material and scrap Groove
- Automatic Reversible Fluid Lubrication System
- Foot paddle
- Double hand control
- Single-continious-interrupted shot options
- PLC applied
- Electric counter
- Security PLC
- Compliance with CE directives
- Press Safety Valve
- Ram Cushioning Cylinders

**Optional Features**

- Speed Control Unit

	Value	Unit
Capacity	200	Ton
Throat Depth	400	mm
Table - Ram Distance	580	mm
Housing Width	650	mm
Ram Adjusment	100	mm
Press Width	1860	mm
Press Height	3300	mm
Press Depth	2200	mm
Table Hole Diameter	Ø255	mm
Table Depth	790	mm
Table Width	1080	mm
Die Tie Hole Diameter	Ø70	mm
Ram Face Size	515 × 890	mm
Table Height From Floor	745	mm
Stroke	10-145	mm
Stroke Per Minute	44	spm
Motor Power	15	kW
Motor Speed	1500	rpm
Weight	12000	kg

A3	ISO 128	HP_200_PK_AEP_HS	Technical Specifications	Page
TASARIM / DESIGNED	Taha Canat	06.02.2023		1/1
ÇİZEN / DRAWN	Taha Canat	06.02.2023		
KONTROL / CHECKED				

HICO MACHINERY AND ENGINEERING LTD. CO. reserves the right to make changes in dimensions without prior notice.