



### Standart Features

- Steel construction body
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 4 guide ram
- Ram adjustment with ratchet system
- Mechanical disc overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap Groove
- Manuel Hand Pump
- Foot paddle
- Double hand control
- Single-continous-interrupted shot options
- PLC applied
- Electric counter
- Security PLC
- Compliance with CE directives
- Press Safety Valve
- Ram Cushioning Cylinders

### Optional Features

- Electric and Timed Automatic Grease Lubrication System
- Speed Control Unit

	Value	Unit
Capacity	80	Ton
Throat Depth	270	mm
Table - Ram Distance	380	mm
Additional Table - Ram Distance	295	mm
Housing Width	440	mm
Ram Adjusment	75	mm
Press Width	1440	mm
Press Height	2540	mm
Press Depth	1540	mm
Table Hole Diameter	Ø175	mm
Table Depth	540	mm
Table Width	750	mm
Die Tie Hole Diameter	Ø45	mm
Ram Face Size	370 × 230	mm
Table Height From Floor	670	mm
Stroke	10-95	mm
Strok Per Minute	56	spm
Motor Power	7,5	kW
Motor Speed	1500	rpm
Approximate Weight	3900	kg

A3	ISO 128	HP_80_PK_AEP_MS	Technical Specifications	Page
TASARIM / DESIGNED	Taha Canat	08.05.2014		1/1
ÇİZEN / DRAWN	Taha Canat	16.12.2021		
KONTROL / CHECKED				

HICO MACHINERY AND ENGINEERING LTD. CO. reserves the right to make changes in dimensions without prior notice.