



Standart Features

- Steel construction body
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 4 guide ram
- Ram adjustment with ratchet system
- Mechanical disc overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap Groove
- Electric and timed automatic grease lubrication
- Foot paddle
- Double hand control
- Single-continious-interrupted shot options
- PLC applied
- Electric counter
- Security PLC
- Compliance with CE directives
- Press Safety Valve
- Ram Cushioning Cylinders

Optional Features

- Speed Control Unit

	Value	Unit
Capacity	150	Ton
Throat Depth	305	mm
Table - Ram Distance	460	mm
Additional Table - Ram Distance	360	mm
Housing Width	470	mm
Ram Adjusment	90	mm
Press Width	1570	mm
Press Height	2880	mm
Press Depth	1780	mm
Table Hole Diameter	Ø205	mm
Table Depth	610	mm
Table Width	850	mm
Die Tie Hole Diameter	Ø50	mm
Ram Face Size	420 × 255	mm
Table Height From Floor	720	mm
Stroke	10-110	mm
Strok Per Minute	53	spm
Motor Power	15	kW
Motor Speed	1500	rpm
Approximate Weight	6200	kg

A3	ISO 128	HP_150_PK_AEP_MS	Technical Specifications	Page
TASARIM / DESIGNED	Taha Canat	08.05.2014		1/1
ÇİZEN / DRAWN	Taha Canat	16.12.2021		
KONTROL / CHECKED				

HICO MACHINERY AND ENGINEERING LTD. CO. reserves the right to make changes in dimensions without prior notice.